

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B25J 15/04, B23K 9/28	A1	(11) International Publication Number: WO 97/26118	(43) International Publication Date: 24 July 1997 (24.07.97)
--	----	---	---

(21) International Application Number: PCT/US97/00639


(22) International Filing Date: 16 January 1997 (16.01.97)

(30) Priority Data:
08/587,367 16 January 1996 (16.01.96) US(71) Applicant: APPLIED ROBOTICS, INC. [US/US]; 648
Saratoga Road, Glenville, NY 12302 (US).(72) Inventors: CULLEN, W., Paul; 518 Riverside Place, Scotia,
NY 12302 (US). BILLINGS, Pamela, B.; 345 Saratoga
Avenue, Ballston Spa, NY 12302 (US). GALLUP, Douglas,
N.; R.D. #2, Box 253A, Schoharie, NY 12157 (US).(74) Agents: JOHNSON, John, T. et al.; Heslin & Rothenberg, P.C.,
5 Columbia Circle, Albany, NY 12203 (US).(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY,
CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL,
IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV,
MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU,
SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN,
ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent
(AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, ML, MR, NE, SN, TD, TG).**Published***With international search report.**Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.*

(54) Title: INTEGRATED STUD WELDING ROBOTIC TOOL CHANGING SYSTEM

(57) Abstract

An apparatus for transporting a plurality of fasteners (27) in an automated changing system, i.e., in a robotic tool changing system (10), wherein the system includes a tooling adaptor assembly (14) adapted to be coupled and decoupled to and from a robot adaptor assembly (12). The transport apparatus includes a first member (62) which has a first passage (66) formed therethrough and a second member (64) which has a second passage (100) formed therethrough. Both the first and second members are mutually adapted for alignment to one another when the adaptor assemblies are coupled. When the adaptor assemblies are coupled together, the first and second members form an interface fitting so that the plurality of fasteners, i.e., studs, may pass through therethrough, and ultimately be transported to a tool, i.e., a stud welding gun (26).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

INTEGRATED STUD WELDING ROBOTIC TOOL CHANGING SYSTEM

BACKGROUND

Technical Field

5 The present invention generally relates to automated changing systems. More particularly, the present invention relates to robotic tool changing systems for stud welding applications.

Background Information

10 Over the past several decades, reliance on robot technology has increased significantly. While at one time the highest concentration of robot use was in the area of electronic machinery manufacturing and automobile manufacturing, the application of robot technology has spread to other diverse areas
15 such as nuclear power generation, offshore development, disaster prevention and to areas where remote-controlled robot systems perform their functions quickly and accurately under difficult and dangerous conditions. Specifically, robots are now
20 used to perform many diverse functions, such as finishing concrete, painting tall buildings and even performing medical care. The economic and social role of robots is likely to continue to expand in the future, as advancements in robot technology generate
25 wider commercial application and provide improvements in industrial productivity and product quality.

One robotic development which has fueled the expansion and utilization of industrial robots are robotic tool changing systems which are designed to
30 facilitate the performance of various different tasks by a single robotic system. For instance, a robotic tool changing system may enable a single robot to

-2-

perform stud and spot welding, to palletize heavy loads and to engage in metal removal operations. The robotic tool changing system allows for the automatic exchange of tools necessary to perform these varied tasks. Typically, a robotic tool changing system is made up of two primary assemblies, a robot adaptor assembly and a tooling adaptor assembly. The robot adaptor assembly is attached to the robot while the tooling adaptor assembly is attached to the tool.

5 When the adaptor assemblies are coupled together, the assemblies form the mechanical connection and signal interface (electrical, pneumatic, etc.), which permits the robot to perform a particular task.

10

Notwithstanding the expansion of robot technology to other fields, robot technology remains significant in industrial applications, such as in automotive manufacturing. For instance, robots continue to play a major role in automotive stud welding. In robotic stud welding applications, a stud welding gun is attached to a robot which is programmed to position the gun to the desired weld location and to automatically produce stud welds, without the need for an operator.

15

20

In a conventional automated stud welding system, system resource utility lines or cables are typically fed directly into the stud welding gun. For example, a stud feed tube, i.e., a hollow utility line or cable, may be fed directly into a stud welding gun to transfer a plurality of studs from a remote stud feeder to the stud welding gun. The remote stud feeder may provide air pressure to transport the studs through the feed tube. As the stud welding gun receives the flow of studs, the stud welding operation may be continuously performed. Another

25

30

-3-

utility line or cable may also be fed directly into the stud welding gun for providing the gun with a weld current. Usually, this cable will extend from a remote power source/controller, providing the
5 necessary current and its duration. Other utility lines may also extend directly into the gun, e.g., pneumatic lines for operating the gun, air or liquid lines for cleaning the weld surface, etc.

Often, during the manufacturing process, it is
10 necessary to exchange stud welding guns. For instance, system failure or periodic maintenance may result in the need to have the robot change the currently employed stud welding gun to a backup or secondary gun. In order to efficiently continue the
15 manufacturing process without loss of production time, it is imperative that an automated method of changing from one stud welding gun to another exists. In order to provide such automation, conventional robotic stud welding systems typically include two
20 stud welding guns for a single work cell. However, as described above, all utilities lines in the conventional system are attached directly to the stud welding guns. A problem associated with attaching all utility lines directly to the stud welding gun is
25 limited changing capability and efficiency, thereby restricting improvements in robot productivity.

Thus, a need exists for a fully integrated robotic tool change system having all stud welding utilities interfaced through the tool changing
30 assemblies. The structure of the present invention, i.e., a robotic system which incorporates all of the utilities directly into a single tool change system for use with stud welding, fulfills this need.

SUMMARY

Briefly, the present invention satisfies this need and overcomes the shortcomings of the prior art through the provision of an apparatus for an
5 automated changing system for transporting fasteners to a tool. A first adaptor assembly has a first passage, wherein this first passage has a first opening at a first end thereof and a second opening at a second end thereof. A second adaptor assembly
10 has a second passage, wherein the second passage has a first opening at a first end thereof and a second opening at a second end thereof. When the first and second adaptor assemblies are mated, the first and second passages are mutually alignable to allow a
15 fastener, e.g., a stud, to be transported therethrough to a tool, e.g., a stud welding tool.

It is therefore a primary object of the present invention to provide a stud welding robotic changing system which integrates all stud welding utility
20 lines through the robotic change system.

It is another object of the present invention to provide a stud welding robotic changing system which increases the life of the utility lines of the stud welding tools employed in the system.

25 It is yet another object of the present invention to provide a stud welding robotic changing system which requires less maintenance and repair over conventional robotic stud welding systems.

It is still another object of the present
30 invention to provide an integrated stud welding robotic changing system which simplifies the

-5-

programmed motion of the robot arm when switching between stud welding tools.

It is but another object of the present invention to provide a stud welding robotic changing
5 system which permits the removal of the stud welding gun from the work cell without the need to manually disconnect the utility lines attached to the stud welding gun.

BRIEF DESCRIPTION OF THE DRAWINGS

10 The subject matter which is regarded as the present invention is particularly pointed out and distinctly claimed in the concluding portion of the specification. The invention, however, both as to
15 organization and method of practice, together with the further objects and advantages thereof, may be best understood by reference to the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a three-dimensional, partially
20 exploded view, of an automated robotic tool changing system, constructed in accordance with the principles of the present invention, and employed in conjunction with a stud welding gun.

FIG. 2 is an isometric view showing the
25 automated tool changing adaptor assemblies of Fig. 1, i.e., a robot adaptor assembly and a tooling adaptor assembly, both coupled together, all constructed in accordance with the principles of the present invention.

-6-

FIG. 3 is a partial cross-sectional and cutaway view of the adaptor assemblies shown in FIG. 2, but shown slightly separated, illustrating in detail the structure of one embodiment of an interface fitting
5 for transporting fasteners, i.e., studs, through a robotic tool changing system.

FIG. 4 is a system diagram illustrating a conventional robotic stud welding system which includes a primary stud welding gun and a secondary
10 stud welding gun, each gun having a dedicated source for all required resources, wherein all the utility lines for the guns are tethered to the ceiling and attached directly to the respective guns.

FIG. 5 is a system diagram illustrating the automated robotic tool changing system, constructed
15 in accordance with the principles of the present invention, comprising a primary stud welding gun and a secondary stud welding gun, wherein the respective utility lines for the guns are fed directly into the
20 automated robotic adaptor assembly of the automated robotic changing system.

DESCRIPTION

It will be readily apparent that the components of the present invention, as generally described and
25 illustrated in the drawings, can be arranged and designed in a wide variety of different configurations. Thus, the following description of the presently preferred embodiments of the integrated stud welding robotic tool changing system, as
30 represented in FIGS. 1 - 5, is not intended to limit the scope of the invention, as claimed, but is merely representative of the presently preferred embodiments

-7-

of the invention. The presently preferred embodiments of the invention will be best understood by reference to the drawings, where like parts are designated with like numerals.

5 In reference to the drawings, and more particularly to FIG. 1, there is shown in accordance with the principles of the present invention, one embodiment of an automated changing system, i.e., an integrated stud welding robotic tool changing system
10 10. Tool changing system 10 includes a first adaptor assembly, i.e., a robot adaptor assembly 12 and a complimentary, automatically couplable, second adaptor assembly, i.e., a tooling adaptor assembly 14. As shown in the exploded view of FIG. 1, robot
15 adaptor assembly 12 is situated over tooling adaptor assembly 14, and both assemblies appear ready to be coupled together.

 Robot adaptor assembly 12 may include a robot adaptor unit 16 and a robot adaptor plate 18. Robot
20 adaptor unit 16 may be removably attached to robot adaptor plate 18 through conventional mechanical securing means, and a robot end of arm 20 may be mechanically secured to robot adaptor plate 18. Likewise, tooling adaptor assembly 14 may include a
25 tooling adaptor unit 22 and a tooling adaptor plate 24. Tooling adaptor assembly 14 may be mechanically secured to a number of different tools, and in the preferred embodiment, to a stud welding gun 26.

 As illustrated best in FIG. 1, various
30 connectors and cables may extend from both robot adaptor unit 16 and tooling adaptor unit 22 so that various applications can be performed by the robotic system 10. Therefore, tool changing system 10 may

-8-

incorporate electrical, pneumatic and other interface connections therein.

A first electrical cable 26, extending from a remote controller (not shown) and into robot adaptor unit 16, facilitates the transfer of input/output (I/O) control signals for the operation of tool changing system 10. During coupling of adaptor units 16 and 22, female electrical pin connector 28 of robot adaptor unit 16 mates with corresponding male electrical pin connector 30 of tooling adaptor unit 22 for electrical control signal transfer between the adaptor units. An associated second electrical cable 32 extends from tooling adaptor unit 22 and is connected to stud welding gun 26.

In order to operate stud welding gun 26, pneumatic lines 34 may extend from a remote source (not shown) into robot adaptor unit 16, and corresponding lines 36 may extend from adaptor unit 22 into gun 26. Female interface ports 38 on robot adaptor unit 16 correspond to male interface ports 40 on tooling adaptor unit 22 so that when adaptor units 16, 22 couple, a passageway provides for the flow of air from pneumatic lines 34, through robot adaptor unit 16 and tooling adaptor unit 22, and out corresponding pneumatic lines 36 of tooling adaptor unit 22 and into stud welding gun 26.

An air line 42 may extend into robot adaptor unit 16, and a corresponding line 44 may extend away from tooling adaptor unit 22 to provide a flow of air from a remote air source (not shown) to ultimately blow-off any debris or other waste which may accumulate on a weld surface. Port 43 on robot adaptor unit 16 corresponds to port 45 on tooling

-9-

adaptor unit 22 for providing a passage for the air through the coupling assemblies. A tubular nozzle 46, extending away from the body of stud welding tool 26, provides the proper aim and direction of the air to clean and prepare the weld surface. Similarly, a fluid line (not shown) may be incorporated into the tool changing system 10 to provide a flow of a fluxing or anti-smut liquid for cleaning and preparing the weld surface.

10 A latching mechanism 48 may be employed in order to automatically couple and uncouple robot adaptor unit 16 to tooling adaptor unit 22. During operation, the engaged latching mechanism 48 provides a payload capacity exceeding the payload requirements of most robots. Pneumatic lines (not shown) provide a flow of air into robot adaptor assembly 12 to operate cylinders (not shown) incorporated therein and employed for securing latching mechanism 48 when coupling and uncoupling the adaptor units.

20 For greater detail on the interconnections and operation of a robotic tool changing system, the reader is referred to U.S. Patent No. 4,664,588, issued to Newell et al., commonly owned by the assignee of the present invention, Applied Robotics, Inc., entitled APPARATUS AND METHOD FOR CONNECTING AND EXCHANGING REMOTE MANIPULABLE ELEMENTS TO A CENTRAL CONTROL SOURCE, the disclosure of which is hereby incorporated by reference in its entirety. Also, the reader is referred to the user's guide for the XChange™ XC-50™ robotic tool changer (user guide 90516R02), of Applied Robotics, Inc., 648 Saratoga Road, Glenville, New York 12302, the disclosure of which is hereby incorporated by reference in its entirety. Currently, the XChange™ XC-50™ tool

-10-

changer is preferred for use in the integrated stud welding robotic tool changing system of the present invention because of its payload capacities. However, it should be understood that the present invention is in no way limited to any particular model or type of robotic exchange equipment. Indeed, the present invention has been designed for incorporation into any automated changing systems for which it is desired to feed all utility lines, including lines for transporting fasteners, directly through automated tool changing assemblies.

Each adaptor assembly of tool changing system 10 may also include an electrical power module, i.e., a robot electrical power module 50 and a tooling electrical power module 52. As can be seen best in FIGS. 1 and 2, each module may be removably secured to a respective adaptor unit. Both modules are configured for matable union when robot adaptor assembly 12 is coupled to tooling adaptor assembly 14. Once mated, sufficient electrical power to operate stud welding gun 26 may be transferred from a remote power source (not shown), through adaptor assemblies 12 and 14, and to gun 26. Preferably, two power cables 51 extend from one or more remote power sources (not shown) into robot electrical power module 50. Extending away from tooling electrical power module 52 and into stud welding tool 26 is a single electrical cable 53 which corresponds to one of the two power cable 51.

As shown in FIG. 1, in order to achieve the transfer of power between the adaptor assemblies, each electrical power module 50, 52 may include one or more high power electrical contacts 54, 55. In the preferred embodiment, each module includes two

-11-

electrical contacts for accommodating two different power requirements. Therefore, two different types of welds, having different amperage requirements, can be performed by tool changing system 10. Each contact
5 54 on robot electrical module 50 is matable with a corresponding contact 55 on tooling electrical module 52 so that electrical power can be transferred between the adaptor assemblies 16 and 22.

It is preferred that the contacts employed in
10 each electrical power module 50, 52 are the replaceable high power electrical contacts which are described in U.S. Patent 5,460,536, issued to Cullen, commonly owned by the assignee of the present
15 REPLACEABLE HIGH POWER ELECTRICAL CONTACTS FOR ROBOTIC TOOL CHANGING SYSTEMS, the disclosure of which is incorporated by reference in its entirety. By using a common hand tool, the replaceable high power contacts provide may be simply and easily
20 replaced without the difficulty of disassembly and re-assembly of the electrical power modules which house the contacts, thereby improving efficiency and productivity in robotic applications.

In order to facilitate coupling of robotic
25 adaptor unit 16 and tooling adaptor unit 22, a plurality of bullet-nosed pins 56 may extend from robot adaptor unit 16 for alignment and insertion into corresponding alignment holes 58 in tooling adaptor unit 22.

30 As illustrated best in FIGs. 2 and 3, robot adaptor unit 16 and tooling adaptor unit 22 may be automatically coupled to one another. In coupling adaptor units together, a connector, i.e., an

-12-

interface fitting 60 may be coupled so as to provide a conduit or passageway for the flow of fasteners, e.g., studs 27, from a remote stud feeder (not shown) to stud welding gun 26. In FIG. 1, studs 27 are
5 illustrated at several different locations as they are transported through tool changing system 10. In the preferred embodiment (and as shown in FIGS. 1 and 2), robotic tool changing system 10 incorporates two interface fittings 60 so as to permit a flow of stud
10 from two separate stud feeders. However, it should be noted that the present invention is in no way limited to two interface fittings 60. Under appropriate circumstances, it may be desirable to employ only a single interface fitting 60. On the
15 other hand, depending upon the robotic application, it may be desirable to have more than two interface fittings 60. For example, it may be desirable to utilize three or four (or more) interface fittings, which could accommodate different sized studs. Such
20 a robotic system could then have the ability to produce different types of stud welds within the robotic work cell.

As can best be seen in FIGS. 2 & 3, each interface fitting 60 may comprise two members, i.e.,
25 a first member 62 and a second member 64, both of which are attached to a respective adaptor assembly. In the preferred embodiment, first member 62 is attached to robot adaptor plate 18 of robot adaptor assembly 12 and second member 64 is attached to
30 tooling adaptor plate 24 of tooling adaptor assembly 14.

First member 62 is preferably tubular in shape and has a first passage 66 extending axially therethrough from a first end 68 to a second end 70.

-13-

A first opening 72, i.e., an entry port, is disposed at first end 68 and a second opening 74, i.e., an exit port, is disposed at second end 70.

First end 68 of first member 62 is preferably attached to a feed tube, e.g., a stud feed tube 76 (shown in FIG. 2). In order to facilitate attachment to stud feed tube 76, first end 68 may include means for attaching stud feed tube 76 thereto. Any known means of attachment may be employed to secure feed tube 76 to first end 68 of first member 62. In one embodiment, and as shown in Fig. 3, a circumferential groove 78 is formed around a periphery of first member 62 for facilitating attachment to a feed tube having a quick-disconnect type connector. However, any connecting means may be employed, so long as the means for connection provides a smooth transition for the transportation of studs from feed tube 76 into first member 62.

First member 62 is preferably secured to an extension member 80 of robot adaptor plate 18. In the preferred embodiment, an aperture 82 is formed in extension member 80 so that first member 62 may be received therein. Any known means of mechanical connection may be employed to secure first member 62 to extension member 80 of robot adaptor plate 18, including, for example, conventional set screws 84. In order to secure set screws 84 to extension member 80, associated threaded apertures 86 may be formed in first member 62. In order to accommodate the formation of threaded apertures 86 in first member 62, a portion of first member 62 preferably includes an enlarged diameter at 87.

-14-

First passage 66 extends from first opening 72 at first end 68 and terminates at second opening 74 at second end 70. Preferably, first passage 66 is circular in cross-section, defines an inner passage wall 88 which provides the conduit for the passage of studs therethrough. As first passage 66 extends from first opening 72 to second opening 74, the inner diameter preferably remains constant. However, in order to facilitate mating of first member 62 and second member 64 so as to provide a smooth transition for studs passing therebetween, a female connector configuration may be formed at second end 70. Therefore, inner passage wall 88 terminates at an inner ledge 92, where the inner diameter of first passage steps up to an inner connector wall 90. Inner connector wall 90 flares outward at 94 to provide a lead-in at second opening 74 for receiving second member 64.

Second member 64 is preferably tubular in shape and has a second passage 100 extending axially therethrough from a first end 102 to a second end 104. A first opening 106, i.e., an entry port, is disposed at first end 102 and a second opening 108, i.e., an exit port, is disposed at second end 104.

First and second members 62, 64 are mutually adapted to be aligned and mated for facilitating transport of studs 27 therethrough. In order to facilitate mating of first member 62 and second member 64, first end 102 of second member 64 may be formed in a male connector configuration for union with the female configuration formed at second end 70 of first member 62.

-15-

Second member 64 may be secured to an extension member 110 of tooling adaptor plate 24. An aperture 112 may be formed in extension member 110 of tooling adaptor plate 24 for receiving second member 64 therein. A ledge 112 may be formed around a periphery of second member 64 to prevent second member 64 from passing through aperture 112. Also, a circumferential groove 114 may be formed around a periphery of second member 64 for receiving a snap ring 116 therein to secure second member to extension member 110.

A spring, e.g., a conventional coil spring 130 may extend around second member 64 to provide a degree of play or compliancy when members 62 and 64 are coupled together. Coil spring 130 is positioned so that one of its ends is positioned to rest against a lip 132 formed around a periphery of second member 64 while its other end rests against extension member 110. Coil spring 130 is preferably integrated into tool changing system 10 of the present invention so as to compensate for collision or gravity changes which could cause adaptor assemblies 12 and 14 to separate. Thus, the incorporation of spring 130 minimizes any structural damage to interface fitting 60 which could occur if there was no compliancy provided. It should be noted that any other means for providing a degree of compliancy for interface fitting 60 may be employed in lieu of coil spring 60.

Second passage 100 extends from first opening 106 at first end 102 and terminates at second opening 108 at second end 104. Like first passage 66, second passage 100 is preferably circular in cross-section and defines an inner passage wall 122. As second passage 100 extends from first opening 102 to second

-16-

opening 104, the inner diameter of inner passage wall 100 preferably remains constant and is the same as the inner diameter of inner passage wall 88 of first member 66. At first end 102, inner passage wall 122
5 may include a chamfered wall 124 to provide a smooth transition for the studs being transferred through interface fitting 60.

At first end 102 of second member 64, the outer periphery of second member 64 may be sized for
10 slidable insertion in to inner connector wall 90 of first member 62. Therefore, the inner diameter of inner connector wall 90 and the outer diameter of first outer wall 134 should be configured for
15 slidable union. A ledge 136 is formed at a selected location of the periphery of second member 64 to facilitate placement of the male connector configuration of second member 64 within the female connector configuration of first member 62.

A circumferential gap 138 is formed around a
20 periphery of first outer wall 134 to accept an O-ring 140 therein. While studs are being passed through mated members 62 and 64, the air pressure associated with transporting studs through interface fitting 60 forces O-ring 140 to rest up against inner connector
25 wall 90 of first member 62 to create a leak-free seal between members 62 and 64.

Second end 104 of second member 64 is preferably attached to a feed tube 118 which is fed into stud welding gun 26. In order to facilitate attachment to
30 stud feed tube 118, second end 104 may include means for attaching stud feed tube 118 thereto. Any known means of attachment may be employed to secure feed tube 118 to second end 104 of second member 64. As

-17-

shown in Fig. 3, a circumferential groove 120 may be formed around a periphery of second member 64 near second end 104 for facilitating attachment to a feed tube with a quick-disconnect type connector.

5 However, any connecting means may be employed, so long as the means for connection provides a smooth transition for the transportation of studs from second member 64 into feed tube 118.

In reference now to FIG. 4, there is shown a complete conventional robotic stud welding system 200. This conventional system includes a robot 202 having an arm 204 with various pivot points located therealong. A primary stud welding gun 206, labeled TOOL 1, is shown secured to the end of arm 208 of robot 202, while a secondary stud welding gun 210, labeled TOOL 2, is shown stationed on a fixture 212 for backup. An empty fixture 214 awaits placement of primary stud welding gun 206 thereon when the robot changes from primary gun 206 to secondary stud welding gun 210. A primary source 216, labeled SOURCE 1, represents the supply source for primary stud welding gun 206 and a secondary source 218, labelled SOURCE 2, provides the resources for secondary stud welding gun 210. While all of the resources appear to be derived from either primary source 216 (SOURCE 1) or secondary source 218 (SOURCE 2), it is likely that there will be separate physical components which provide the varied resources. For example, the stud feeding apparatus may be separate from the electrical power supply. All of the resources emanating from primary and secondary sources 216, 218 are represented by two lines, respectively, line 220 and line 222. However, in actuality, they would represent a bundle of lines or cables meshed together, like an umbilical cord.

-18-

All lines are tethered to hooks 224 depending from a ceiling 226 where the system is located and the utility lines are draped from various points on the ceiling. The draping and tethering of the
5 umbilical cord-like mesh of lines results in wear on the lines. Furthermore, instead of attaching all utility lines of the system 200 directly into a robot adaptor assembly of a robotic tool changing system, like the system of the present invention, all utility
10 lines or cables are fed directly into respective stud welding guns. Therefore, all utility cables emanating from primary source 216 (SOURCE 1) are directly attached to primary stud welding gun 206 (TOOL 1) and all utility cables emanating from
15 secondary source 218 (SOURCE 2) are directed attached to secondary stud welding gun 210 (TOOL 2).

If for some reason, it is necessary to change from primary stud welding gun 206 to secondary stud welding gun 210, i.e., for maintenance or because of
20 system failure, primary gun 206 may be placed on primary fixture 214, and the robot may thereafter grasp secondary stud welding gun 210. If it is necessary to remove primary stud welding gun 206 from the work cell, it will be necessary to have a worker
25 manually remove all utility lines fed directly into primary tool 206. Upon return of primary stud welding gun 206 to the work cell for continued operation, all utilities lines emanating from line 220 need to be manually reconnected to primary stud
30 welding gun 206.

FIG. 5 illustrates a complete robotic stud welding system 300 constructed in accordance with the principles of the present invention. This system includes a robot 302 having an arm 304 with various

-19-

pivot points located therealong. A robotic tool changing system is incorporated into stud welding system 300, and therefore robot and tooling adaptor assemblies 306, 308 are coupled to one another, and
5 robot adaptor assembly 306 is attached to the end of arm 310 of robot 302. A primary stud welding gun 312, labelled TOOL 1, is shown secured to the tooling adaptor assembly 308, while a secondary stud welding gun 314 is stationed on a fixture 316 as a backup
10 unit for the stud welding system. An empty fixture 317 awaits placement of primary stud welding gun 312 thereon when the robot changes from primary gun 312 to secondary stud welding gun 314. Secondary stud welding gun 314 includes a tooling adaptor assembly
15 318 attached thereto to be coupled to robot adaptor assembly 306.

A primary source 320, labelled SOURCE 1, represents a source of supply for all desired resources for primary stud welding gun 312 (TOOL 1),
20 including electrical power, pneumatic supply, control (I/O) and stud feed. A secondary source 322, labelled SOURCE 2, provides the resources for secondary stud welding gun 314 (TOOL 2). It should be noted that while in FIG. 4 all of the resources
25 appear to be derived from a single central physical location, either primary source 320 (SOURCE 1) or secondary source 322 (SOURCE 2), it is likely that there will be separate physical components which provide the varied resources. For example, the stud
30 feeding apparatus may be separate from the electrical power supply. However, it should also be noted that the present invention could utilize a single source of resources for primary gun 312 and secondary gun 314, thereby eliminating repetitive resource devices.

-20-

A first line 324, representing the transfer of all of the resources emanating from primary source 320 (SOURCE 1), extends away from primary source 320, up and along robot arm 304 and into robot adaptor assembly 306. Similarly, a second line 326, representing the transfer of all of the resources emanating from secondary source 322, extends away from secondary source 322, up and along robot arm 304, and into robot adaptor assembly 306. While all the resources emanating from primary and secondary sources 320, 322 are each represented as a single line in FIG. 5, in actuality, they would represent a bundle of lines or cables. Significantly, all of the utility lines extending from SOURCE 1 and SOURCE 2 for respective primary and secondary guns 312, 314 are joined directly to a single robot adaptor assembly 306. Because the utilities may extend from separate sources into a single robot adaptor assembly 306, it may be necessary to provide a junction connector or a manifold (both not shown) for passing some of the resources through the adaptor assemblies. However, in the preferred embodiment, this is not necessary for transporting studs because the preferred embodiment envisions two interface fittings for accommodating two stud feeders.

While several aspects of the present invention have been described and depicted herein, alternate aspects may be effected by those skilled in the art to accomplish the same objectives. For example, while in the preferred embodiment the subject invention is directed to transferring studs between adaptor assemblies, it is contemplated that the subject invention may be utilized for transferring other types of fasteners and solid items between automated robotic exchange units. Also, while in the

-21-

preferred embodiment two interface fittings are contemplated, it should be understood that any number of interface fittings may be incorporated into the robotic tool changing system as described herein.

- 5 Moreover, while two sources of resources are contemplated, any number of sources may be incorporated into the present invention, including, for example, a single source of resources. Accordingly, it is intended by the appended claims to
- 10 cover all such alternative aspects as fall within the true spirit and scope of the invention.

-22-

CLAIMS

What is claimed is:

1. An apparatus for an automated tool changing system for transporting a fastener to a tool, comprising:

5 a first adaptor assembly having a first passage, said first passage having a first opening at a first end thereof and a second opening at a second end thereof;

10 a second adaptor assembly having a second passage, said second passage having a first opening at a first end thereof and a second opening at a second end thereof; and

15 wherein when said first and second adaptor assemblies are mated, said first and said second passages are mutually alignable to allow a fastener to be transported therethrough to a tool.

2. The apparatus of claim 1, further comprising means for aligning said second opening of said first passage to said first opening of said second passage.

3. The apparatus of claim 2, wherein said alignment means comprises a female connector disposed at said second end of said first passage.

4. The apparatus of claim 3, further comprising means for aligning said first opening of said second passage to said second opening of said first passage.

5. The apparatus of claim 4, wherein said alignment means comprises a male connector disposed at said first end of said second passage, said male

-23-

and female connectors being mutually adapted to be
5 aligned for facilitating transport of a fastener
through said first and second passages when said
first and second adaptor assemblies are mated.

6. The apparatus of claim 1, further comprising
a first member attached to said first adaptor
assembly, said first passage being formed through
said first member.

7. The apparatus of claim 6, further comprising
a second member attached to said second adaptor
assembly, said second passage being formed through
said second member.

8. The apparatus of claim 7, further comprising
means for aligning said first and second members for
facilitating transport of a fastener through said
first and second passages.

9. The apparatus of claim 8, wherein said
alignment means comprises:

a female connector formed at said second
end of said first passage;

5 a male connector formed at said first end
of said second passage;

said male and female connectors being
matable when said first and second adaptor
assemblies are mated.

10. The apparatus of claim 1, further
comprising a connector for connecting a feed tube to
said first end of said first passage.

-24-

11. The apparatus of claim 1, further comprising a connector for connecting a feed tube to said second end of said first passage.

12. A fitting for transporting a fastener in an automated changing system, comprising:

5 a first member for incorporation on a first adaptor assembly, said first member having a first passage extending from a first end thereof to a second end thereof;

an entry port disposed at said first end of said first member and an exit port disposed at said second end of said first member;

10 means for attaching said first end to a feed tube; and

means for aligning said second end to a second member so as to allow a fastener to pass through said first member to said second member.

13. The fitting of claim 12, further comprising:

5 a second member for incorporation on a second adaptor assembly, said second member having a second passage extending from a first end thereof to a second end thereof;

an entry port disposed at said first end of said second member and an exit port disposed at said second end of said second member;

10 means for aligning said first end of said second member to said second end of said first member so as to allow a fastener to pass through said first and second passages; and

15 means for attaching said second end of said second member to a tube attached to a tool.

-25-

14. The fitting of claim 12, wherein said means for aligning said second end to said second member comprises a female connector disposed at said second end of said first member.

15. The fitting of claim 14, wherein said means for aligning said first end of said second member comprises a male connector disposed at said first end of said second member, said male and female
5 connectors being mutually adapted to permit a fastener to pass through said first and second passages.

16. In a robotic changing system, the combination comprising:

a robot adaptor assembly;
a tooling adaptor assembly adapted to be
5 coupled and decoupled to and from said robot adaptor assembly;
a first passage formed on said robot adaptor assembly, said first passage having an entry port at a first end thereof and an exit
10 port at a second end thereof;
a second passage formed on said tooling adaptor assembly, said second passage having an entry port at a first end thereof and an exit port at a second end thereof; and
15 wherein when said robot adaptor assembly and said tooling adaptor assembly are coupled, said first and second passages define a passageway extending from said entry port of said first passage to said exit port of said
20 second passage to allow a fastener to be transported therethrough to a tool.

-26-

17. The combination of claim 16, further comprising a first member attached to said robot adaptor assembly, said first passage being formed through said first member.

18. The combination of claim 17, further comprising a second member attached to said tooling adaptor assembly, said second passage being formed through said second member.

19. The combination of claim 18, further comprising means for aligning said first and second members such that when said assemblies are coupled, said exit port of said first passage and said entry
5 port of said second passage are contiguous.

20. An apparatus for transporting a fastener in an automated changing system, said automated changing system including a first adaptor assembly adapted to be coupled and decoupled to and from a second adaptor
5 assembly, said apparatus comprising:

a first member having a first passage formed therethrough, said first member being attachable to said first adaptor assembly;

a second member having a second passage
10 formed therethrough, said second member being attachable to said second adaptor assembly; and


said first and second members being mutually adapted for alignment to one another when said adaptor assemblies are coupled so as
15 to permit a fastener to pass through said first passage of said first member and said second passage of said second member.

-27-

21. The apparatus of claim 20, wherein said first passage of said first member extends from a first end thereof to a second end thereof, said first member including attachment means disposed at said second end.

22. The apparatus of claim 21, wherein said second passage of said second member extends from a first end thereof to a second end thereof, said second member including attachment means disposed at said first end, said first and second members being mutually adapted to be aligned when said first and second adaptor assemblies are coupled so that a passageway is formed through said first and second members.

1 / 3



2 / 3

FIG. 2







FIG. 3



3/3

**FIG. 4****FIG. 5**

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/00639

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B25J15/04 B23K9/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B25J B23K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 664 588 A (NEWELL) 12 May 1987 cited in the application see column 2, line 27 - line 49 see column 3, line 10 - line 57 ---	1-5,10, 11,16
Y	US 3 309 495 A (SHOUP) 14 March 1967 see column 2, line 13 - column 4, line 10 ---	1-5,10, 11,16
A	EP 0 216 261 A (CHIRON WERKE GMBH) 1 April 1987 see page 18, line 16 - page 19, line 8; figure 2 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

14 May 1997

Date of mailing of the international search report

17. 06. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Lamineur, P

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/00639

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4664588 A	12-05-87	CA 1251809 A	28-03-89
		EP 0154227 A	11-09-85
		JP 1660259 C	21-04-92
		JP 3025310 B	05-04-91
		JP 60213494 A	25-10-85

US 3309495 A	14-03-67	NONE	

EP 216261 A	01-04-87	DE 3620343 A	26-03-87
		BR 8604580 A	26-05-87
		JP 62068246 A	28-03-87
		US 4716647 A	05-01-88
